

WHAT IS CLAIMED IS:

a 1 1. A graphics and video controller comprising:  
2 an ~~dual aperture~~ interface for receiving words  
3 of pixel data, each said word associated with an address  
4 buffer;  
5 circuitry for writing each said word of said  
6 pixel data received by said interface to a one of  
7 on-screen and off-screen memory areas of a frame buffer;  
8 circuitry for selectively retrieving said words  
9 from said on-screen and off-screen areas;  
a 10 a first pipeline for processing words of ~~pixel~~ <sup>graphics</sup>  
11 data retrieved from said frame buffer; and  
12 a second pipeline for processing words of  
c 13 <sup>video</sup> ~~graphics~~ data retrieved from said frame buffer.

B 1 2. The <sup>controller</sup> ~~system~~ of Claim 1 and further comprising  
2 output selection circuitry for selecting for output  
3 between graphics data received from said first pipeline  
4 and data received from said second pipeline, said  
5 selection circuitry operable to:  
6 in a first mode, pass data from said first  
7 pipeline; and  
8 in a second mode, pass data from said second  
9 pipeline when said data corresponds to a selected display  
10 position of a display window.

1 3. The controller of Claim 2 wherein said  
2 selection circuitry is further operable to:  
3 in a third mode, pass data from said second  
4 pipeline when said data corresponds to said selected  
5 display position of said display window and data from  
6 said first pipeline match a color key.

32

1        4.    The controller of Claim 3 wherein said  
2    selection circuitry is further operable in a fourth mode  
3    to pass data from said second pipeline when data from  
4    said first pipeline match a color key.

1        5.    The controller of Claim 1 wherein said  
2    circuitry for retrieving maintains a stream of graphics  
3    data to said first pipeline and provides video data to  
4    said second pipeline when a display raster scan reaches  
5    said display position of said window.

1        6.    The controller of Claim 1 and further  
2    comprising:  
3        a video port for receiving real-time video  
4    data; and  
5        circuitry for generating an address to said  
6    memory at which said real-time video data is to be  
7    stored.

1        7.    The controller of Claim 1 wherein said second  
2    pipeline includes a first first-in-first-out memory for  
3    receiving data for a first display line of pixels in  
4    memory and a second first-in-first-out memory <sup>A</sup> or  
5    receiving data from a second display line of pixels in  
6    memory.

1        8.    The controller of Claim 7 wherein said first  
2    display line adjacent in memory to said second display  
3    line.

1        9.    The controller of Claim 7 wherein said output  
2    selection circuitry comprises:           

33

3 an output selector for selecting between data  
4 from said second pipeline and data from said first  
5 pipeline in response to a selection control signal;  
6 a register for maintaining a plurality of  
7 overlay control bits;  
8 window position control circuitry for  
9 selectively generating a position control signal when a  
10 word of said data stream from said second pipeline falls  
11 within a display window;  
12 color comparison circuitry for comparing words  
13 of said data stream from said first pipeline with a color  
14 key and <sup>for providing</sup> ~~provide~~ in response a color comparison control  
15 signal; and  
16 a control selector for selectively providing a  
17 said selection control signal in response to said overlay  
18 control bits in said register and at least one of said  
19 position control and color comparison control signals.

10. The <sup>controller</sup> ~~overlay control circuitry~~ of Claim 9  
wherein said window position control circuitry comprises:  
window position counters operable to increment  
from initial count values corresponding to a starting  
pixel of a display window as data representing each pixel  
in a display screen is pipelined through said overlay  
control circuitry;  
screen position counters operable to count as  
data representing each pixel in said display screen is  
pipelined through said overlay control circuitry; and  
comparison circuitry operable to compare a  
current count in said window position counters and a  
current count in said screen position counters and  
selectively generate said position control signal in  
response.

34

11. The ~~overlay control circuitry~~ <sup>controller</sup> of Claim 9 wherein said color comparison circuitry comprises:

- a color key register for storing bits composing said color key; and
- a plurality of AND-gates for comparing said words of said graphics data stream with bits of said color key.

Sub B  
a

12. A controller comprising:

- a ~~dual-aperture~~ port for receiving video and graphics data, a word of said data received with an address directing said word to be processed as a word of video data or a word of graphics data;
- a second port for receiving real-time video data;
- circuitry for generating an address associated with a selected one of said memory spaces for a word of said real-time video data;
- circuitry for writing selectively each word of data into a selected one of on-screen and off-screen memory spaces of a frame buffer;
- circuitry for selectively retrieving said words of data from said on-screen and off-screen spaces as data is rastered for driving a display;
- a graphics backend pipeline for processing ones of said words of data representing graphics data retrieved from said frame buffer;
- a video backend pipeline for processing other ones of said words of data representing video data retrieved from said frame buffer, said circuitry for retrieving always rastering a stream words of data from said frame buffer to said graphics pipeline and rastering video data to said video backend pipeline when a display raster scan reaches a display position of a window;

35

27 output selector circuitry for selecting for  
28 output between words of data output from said graphics  
29 backend pipeline and words of data output from said video  
30 backend pipeline.

1 <sup>14</sup> 13. The controller of Claim <sup>13</sup> 12 wherein said output  
2 selector is further operable to select between graphics  
3 data output from a color look-up table and true color  
4 data output from said graphics pipeline.

*Sub-B* 1 14. The controller of Claim 13 wherein said output  
2 selector is operable to:  
3 in a first mode, pass only a word of data  
4 output from said graphics pipeline;  
5 in a second mode, pass a word of data output  
6 from said video pipeline when said display raster scan  
7 has reached a display position corresponding to a window  
8 and a word of data from said graphics pipeline otherwise;  
9 in a third mode, pass a word of data output  
10 from said video pipeline when said display raster scan  
11 has reached a display position corresponding to a window  
12 and a corresponding word of data from said graphics  
13 pipeline matches a color key and a word of data from said  
14 graphics pipeline otherwise; and  
15 in a fourth mode, pass a word of data from said  
16 video pipeline when said a corresponding word of data  
17 from said graphics pipeline matches a color key and a  
18 word of data from said graphics pipeline otherwise.

1 <sup>16</sup> 15. The controller of Claim <sup>13</sup> 12 wherein said video  
2 pipeline includes a first first-in-first-out memory for  
3 receiving a plurality of words of data for a first  
4 display line of pixels in memory and a second  
5 first-in-first-out memory or receiving a plurality of

6 words of data from a second display line of pixels in  
7 memory.

1 <sup>13</sup> 16. The controller of Claim <sup>16</sup> 15 wherein said first  
2 display line is stored adjacent in memory to said second  
3 display line.

*Sub 33* 1 17. The controller of Claim 12 wherein said output  
2 selector circuitry comprises:  
3 a control selector having a plurality of data  
4 inputs coupled to a register, said register storing a  
5 plurality of overlay control bits;  
6 window position control circuitry coupled to a  
7 first control input of said control selector, said window  
8 position control circuitry operable to selectively  
9 provide a first control signal to said first control  
10 input when a word of data being pipelined through said  
11 video pipeline falls within a display window;  
12 color comparison circuitry operable to compare  
13 a word of data being pipelined through said graphics  
14 pipeline with a color key and provide in response a  
15 second control signal to a second control input of said  
16 control selector; and  
17 wherein said control selector is operable to  
18 provide an output selection control signal to said  
19 control input of said output selector in response to at  
20 least one of said first and second control signals and  
21 said overlay control bits being stored in said register.

1 18. The circuitry of Claim 17 wherein said output  
2 selector circuitry further includes a third input coupled  
3 to a second output of said graphics pipeline, said output  
4 selector further operable to select between data pipeline  
5 on said respective video and graphics pipelines in

6 response to a bit presented at a second control input to  
7 said output selector.

1 <sup>20</sup> 19. The circuitry of Claim <sup>18</sup> 17 wherein said window  
2 position control circuitry comprises:

3 a window x-position counter operable to count  
4 from a loaded x-position value in response to a video  
5 clock, said x-position counter reloading in response to  
6 display horizontal synchronization signal;

7 a window y-position counter operable to count  
8 from a loaded y-position value in response to said  
9 horizontal synchronization signal, said y-position  
10 counter reloading in response to a display vertical  
11 synchronization signal;

12 CRT position circuitry operable maintain counts  
13 corresponding to a current display pixel; and

14 comparison circuitry operable to compare  
15 current counts in said window counters with said current  
16 counts held in said CRT position circuitry and generate  
17 in response said first control signal.

1 <sup>21</sup> 20. The circuitry of Claim <sup>20</sup> 19 wherein said window  
2 position control circuitry further comprises an x-  
3 position register for holding said x-position value for  
4 loading into said x-position counter and a y-position  
5 register for holding said y-position value for loading  
6 into said y-position counter.

1 <sup>22</sup> 21. The circuitry of Claim <sup>13</sup> 20 wherein said color  
2 comparison circuitry comprises:

3 a color key register for storing a plurality of  
4 color key bits; and

5 a plurality of XNOR-gates each having at least  
6 one input coupled to a bit position in said color key

38

7 register and at least one input coupled to said graphics  
8 data path.

1 ~~23~~<sup>13</sup>. The circuitry of Claim ~~12~~<sup>13</sup> wherein said video  
2 pipeline comprises:

3 a first-in/first-out memory for receiving a  
4 first stream of words of data from said frame buffer;

5 a second first-in/first-out memory disposed in  
6 parallel with said first first-in/first-out memory for  
7 receiving a second stream of words of data from said  
8 frame buffer; and

9 interpolation circuitry for selectively  
10 generating an additional word of data by interpolating a  
11 word of said first stream and a word of second stream  
12 data output from said first and second first-in/first-out  
13 memories.



*a* 25  
23. A display system comprising:  
2 a first backend pipeline for processing  
3 ~~playback video~~ data;  
4 a second backend pipeline for processing  
5 graphics data disposed in parallel to said first  
6 processing pipeline;  
7 a multi-format frame buffer memory having  
8 on-screen and off-screen areas each operable to  
9 simultaneously store data in graphics and video formats;  
*a* 10 a ~~dual-aperture~~ input port for receiving both  
11 graphics and video data, each word of said data  
12 associated with an address directing said word to be  
13 processed as either graphics or video data;  
14 circuitry for writing a word of said playback  
15 data into a selected one of said areas of said  
16 multi-format memory;  
17 memory control circuitry for controlling the  
18 transfer of data between said first backend pipeline and  
19 said frame buffer and between said second backend  
20 pipeline and said frame buffer;  
21 a display unit; and  
22 overlay control circuitry for selecting for  
23 output to said display unit between data provided by said  
24 first backend pipeline and data provided by said second  
25 backend pipeline.

✓ 26  
24. The display system of Claim 23 wherein said  
2 second backend pipeline includes:  
3 a first first-in-first-out memory for receiving  
4 first selected data;  
5 a second first-in-first-out memory disposed in  
6 parallel to said first first-in-first-out memory for  
7 receiving second selected data;

40

8 interpolation data for generating additional  
9 data by interpolating data output from said respective  
10 first and second first-in-first-out memories.

1 <sup>27</sup>/<sub>25</sub>. The display system of Claim <sup>26</sup>/<sub>24</sub> wherein said  
2 second backend pipeline further comprises color  
3 conversion circuitry for converting data received from  
4 said frame buffer in a video format to a graphics format.

1 <sup>28</sup>/<sub>26</sub>. The display system of Claim <sup>25</sup>/<sub>23</sub> and further  
2 comprising a video front-end pipeline for inputting video  
3 data into a selected one of on-screen and off-screen  
4 spaces of said frame buffer comprising:

5 a video data port for receiving video data from  
6 a real time data source;

7 input control circuitry for receiving framing  
8 signals associated with said real time data and  
9 generating corresponding addresses to said selected one  
10 of said spaces in response.

1 <sup>29</sup>/<sub>27</sub>. The display system of Claim <sup>28</sup>/<sub>26</sub> wherein said  
2 video front-end pipeline further comprises encoding  
3 circuitry for packing said video data prior to storage in  
4 said selected one spaces.

1 <sup>30</sup>/<sub>28</sub>. The display system of Claim <sup>28</sup>/<sub>26</sub> wherein said  
2 video front-end pipeline further comprising multiplexing  
3 circuitry for selecting between video data received  
4 through said video data port and data received from said  
5 dual aperture port.

1 <sup>31</sup>/<sub>29</sub>. The display system of Claim <sup>30</sup>/<sub>28</sub> wherein said  
2 video front end pipeline further comprises conversion  
3 circuitry for converting graphics data received through

- 4 said dual-aperture port to a video format for storage in
- 5 said selected one of said spaces.

42

34  
30. A display data processing system comprising:  
circuitry for writing data into an on-screen  
space of a frame buffer;  
circuitry for writing data into an off-screen  
space of said frame buffer;  
a video pipeline for processing data output  
from ~~said~~ a selected one of said on-screen and off-screen  
spaces comprising:  
a first first-in-first-out memory for  
receiving selected data from said selected space;  
a second first-in-first-out memory  
disposed in parallel to said first first-in-first-  
out memory for receiving other selected data from  
said selected space; and  
an interpolator for generating additional  
data by interpolating data output from said  
respective first and second first-in-first-out  
memories;  
a graphics pipeline disposed in parallel to  
said video pipeline for processing data output from a  
selected one of said on-screen and off-screen spaces; and  
an output selector for selecting between data  
output from said video pipeline and data output from said  
graphics pipeline.

35  
31. The system of Claim ~~30~~ <sup>34</sup> and further comprising  
selection control circuitry for generating an output  
control signal for controlling said output selector  
comprising:  
a control selector having a plurality of data  
inputs coupled to a register, said register for storing  
a plurality of overlay control bits; and  
color comparison circuitry operable to compare  
bits of data output from said graphics pipeline with a

10 color key and provide in response a control signal to a  
11 control input of said control selector.

11 <sup>36</sup>32. The system of Claim <sup>34</sup>30 and further comprising  
2 window position control circuitry operable to provide a  
3 second control signal to a second control input of said  
4 control selector when data from said video pipeline falls  
5 within a display window.

Add  
A1

44